


Constructional Data Form for Photovoltaic Modules

License Holder..... (full address)	Sany Silicon Energy (Zhuzhou) Co., Ltd. Room 518-50, Building 1, Longxin International, No.255, Tongxia Road, Tongtangwan Street, Shifeng District, Zhuzhou City, Hunan Province, P.R. China			
Production Factory..... (full address)	Sany Silicon Energy (Zhuzhou) Co., Ltd. Sany Energy Equipment Industrial Park, No.320 Qingshui Road, Shifeng District, Zhuzhou City, Hunan Province 412005 P.R. China			
Type of Product.....	Photovoltaic (PV) Modules			
Trademark.....				
	Glass-backsheet module			
	With ½ cut of 182 mono c-Si cell (144pcs):	With ½ cut of 182 mono c-Si cell (120pcs):	With ½ cut of 182 mono c-Si cell (108pcs):	-
Type Name or Model No.....	SYM144TSxxx xxx=power in Wp	SYM120TSxxx xxx=power in Wp	SYM108TSxxx xxx=power in Wp	-
Maximum System Voltage [VDC]	1500	1500	1500	-
Rated Maximum Power [W].....	560, 565, 570, 575, 580, 585	460, 465, 470, 475, 480	420, 425, 430, 435, 440	-
Tolerance of Rating Pmax / Voc / Isc [%].....	±3 / ±3 / ±3	±3 / ±3 / ±3	±3 / ±3 / ±3	-
Rated Open Circuit Voltage [V].....	50.47, 50.60, 50.74, 50.88, 51.02, 51.16	42.05, 42.22, 42.38, 42.54, 42.71	38.11, 38.30, 38.49, 39.08, 39.27	-
Rated Short Circuit Current [A].....	14.15, 14.23, 14.31, 14.39, 14.47, 14.56	13.95, 14.07, 14.15, 14.23, 14.31	14.07, 14.15, 14.23, 14.31, 14.39	-
Over-current protection rating[A]:	25	25	25	-
Classification (IEC 61730).....	Class II	Class II	Class II	-
Fire rating (According to UL 790).....	Class C	Class C	Class C	-
Pollution degree	I	I	I	-
Dimensions (l x w x h) [mm]	2278x1134x30	1903*1134*30	1722*1134*30	-
Module area [m²].....	2.58	2.16	1.95	-
Min- creepage	12.3±1	12.3±1	12.3±1	-

Shanghai, 2023-10-18


TÜV Rheinland Group

Zhuzhou

(City)

2023-10-18

(Date)



(Stamp and/or signature of applicant)

Constructional Data Form for Photovoltaic Modules

distance [mm]				
Number of solar cells	144	120	108	-
Cells per bypass diode	48	40	36	-
Serial/parallel connection of cells	SPS	SPS	SPS	-

Shanghai, 2023-10-18


TÜV Rheinland Group

Zhuzhou

(City)

2023-10-18

(Date)



(Stamp and/or signature of applicant)

Constructional Data Form for Photovoltaic Modules

Copy of marking plate:



PV MODULE

Sany Silicon Energy (Zhuzhou) Co., LTD
Sany Energy Equipment Industrial Park,
No.320 Qingshui Road, Shifeng District,
Zhuzhou City, Hunan Province
412005 China
www.sanygroup.com/

SYM144TS560

Max. power (P_{max})
Max. power tolerance
Voltage at max. power (V_{mpp})
Current at max. power (I_{mpp})
Open-circuit voltage (V_{oc})
Short-circuit current (I_{sc})
Maximum system voltage

560W
± 3%
41.77V
13.41A
50.47V ± 3%
14.15A ± 3%
1500VDC

Series Fuse Rating 25A
operating temperature range 40°C ~ +85°C
protect rage II
module wprotecteigh 28.0(kg)
module size 2278×1134×30(mm)
STC 1000W/m², AM1.5, 25°C



warning

Only the professionals can install and
maintain the components Be careful of the
dangerous high DC voltage when connecting
the components Never damage or scratch the
back of the assembly

Shanghai, 2023-10-18


TÜV Rheinland Group

Zhuzhou

(City)

2023-10-18

(Date)



(Stamp and/or signature of applicant)

Constructional Data Form for Photovoltaic Modules

List of Critical Components (add lines for multiple material sources)					
Object	Manufacturer / trademark	Type / model	Technical data / ratings	Standard (if applicable)	Certificates (if applicable)
Front cover	Hunan Kibing Solar Technology Co., Ltd.	External AR Coating Tempered Glass	Thickness = 3.2mm	—	—
Rear cover	Jolywood (Suzhou) Sunwatt Co., Ltd.	FFC-JW3010 (Plus) white	Thickness = 0.310mm (FFC/PET/FFC) (13/285/12um) System voltage = 1500V TI mechanical and electrical @ 20,000h is 124°C Color: White	2 PfG 1793 / 11.17	Q 50492482
Encapsulation material	HANGZHOU FIRST APPLIED MATERIAL CO., LTD	TF4 (near glass)	Thickness = 0.5mm gram weight: 380 g/m ²	—	—
		F806W (near backsheet)	Thickness = 0.5mm gram weight: 420 g/m ²		
Solar cell	Sany Silicon Energy (Zhuzhou) Co., Ltd.	SYCN182T16	N type mono c-Si cell with 16 dotted busbars 182mm x 91mm	—	—
Cell connectors 1	Changzhou Sheng Yue metal new material Co., Ltd.	Sn60Pb40	Ø = 0.26 ± 0.01mm	—	—
Cell connectors 2	Suzhou YourBest New-type Materials Co., Ltd.	Sn60Pb40	Ø = 0.26 ± 0.01mm	—	—
String connectors 1	Changzhou Sheng Yue metal new material Co., Ltd.	Sn60Pb40	T(mm) x L(mm): 0.4mm x 6.0mm 0.4mm x 4.0mm	—	—
String connectors 2	Suzhou YourBest New-type Materials Co., Ltd.	Sn60Pb40	T(mm) x L(mm): 0.4mm x 6.0mm 0.4mm x 4.0mm	—	—
Frame parts	CHANGSHU DONGNENG SOLAR TECHNOLOGY CO., LTD	Anodized Aluminium Alloy 6005-T6 (Silver)	H(mm) x W(mm): 30x35mm (long frame) 30x25mm (short frame)	—	—

Shanghai, 2023-10-18


TÜV Rheinland Group

Zhuzhou

(City)

2023-10-18

(Date)



(Stamp and/or signature of applicant)

Constructional Data Form for Photovoltaic Modules

List of Critical Components (add lines for multiple material sources)					
Object	Manufacturer / trademark	Type / model	Technical data / ratings	Standard (if applicable)	Certificates (if applicable)
Adhesive (frame)	Shanghai Huitian New Material Co., Ltd.	HT906Z	Color: White	—	—
Fluxing agent 1	Zhuhai Changxian New Materials Technology Co., Ltd	CX700	—	—	—
Fluxing agent 2	ASAHI SOLDER TECHNOLOGY(WUXI) CO., LTD	SF180	—	—	—
Fixing tape 1	SuZhou Rongzhi Electronic Technology Co., Ltd	D60F6-2	Thickness= 100µm±40µm	—	—
Fixing tape 2	Guangdong Sunrui New Material Co., Ltd.	HZ UV-100	Thickness= 100µm±40µm	—	—
Insulation tape	—	—	—	—	—
(Optional) Accessories	—	—	—	—	—
Junction box	QC Solar (Suzhou) Corporation	3Qxy (x=1 or 2 or 3 or 4; y=1 or 2 or 3 or 4)	Rated voltage =1500VDC Rated current =20A (x=1; y=1 or 2 or 3 or 4) Rated current =22A (x=2; y=1 or 2 or 3) Rated current =25A (x=3; y=1 or 2 or 3 or 4) Rated current =30A (x=4; y=1 or 2 or 3 or 4) Reverse current=40A IP68	IEC 62790: 2020 EN IEC 62790: 2020	R 50510013
Cable	QC Solar (Suzhou) Corporation	62930 IEC 131 1 x 2,5mm ² / 1 x 4,0mm ² / 1 x 6,0mm ² / 1 x 10,0mm ² HALOGEN FREE LOW SMOKE	Max. Voltage = 1500VDC	IEC 62930	R 50447239
Connector	QC Solar (Suzhou) Corporation	QC4.10-cds	Max. Voltage = 1500VDC Max. Current = 41A	IEC 62852: 2014	R 50505605
Bypass diode	QC Solar (Suzhou) Corporation	QCM2545	Tj max =200 °C;	—	—

Shanghai, 2023-10-18


TÜV Rheinland Group

Zhuzhou

(City)

2023-10-18

(Date)



(Stamp and/or signature of applicant)

Constructional Data Form for Photovoltaic Modules

List of Critical Components (add lines for multiple material sources)					
Object	Manufacturer / trademark	Type / model	Technical data / ratings	Standard (if applicable)	Certificates (if applicable)
Adhesive	Shanghai Huitian New Material Co., Ltd.	HT906Z	Color: White	—	—
Potting (junction box)	Shanghai Huitian New Material Co., Ltd.	5299W-S	Color: White	—	—

Shanghai, 2023-10-18


TÜV Rheinland Group

Zhuzhou

(City)

2023-10-18

(Date)



(Stamp and/or signature of applicant)